



- Fully floating 'all terrain' linkage.
- High torque drive motor.
- Relief valve motor protection.
- Manual angling – left or right.
- Heavy duty steel construction.
- Single hydraulic service operation.
- Heavy duty castors.
- Quick hitch or fork frame option.
- Parking stands.
- Choice of brush bristle.
- Choice of 3 sweeping widths.
- Optional water sprinkler system.



A powerful front mounted heavy duty sweeping unit designed primarily for the loader/telescopic handler market. Available in a range of widths, the fully floating hitch mechanism and heavy duty castors make light work of all terrain, whilst the powerful high torque drive with pressure relief protection and manual angling ability, combine to maximise sweeping efficiency. The unit has integrated parking stands for storage and servicing when not in use.

Use	Heavy - Extra heavy duty sweeping
Mounting	Fork lift frame or quick attachment frame (fully floating 'all terrain' linkage).
Power Source	Hydraulic: 40 - 70 litres/min flow rate @ min 140 BAR.
Brush adjustment	Heavy duty, height adjustable castor wheels.
Brush spec	560mm Diameter: Poly, Wire, PolyWire mix.
Angling	Manual. 20 degrees left or right.
Castors	203mm Diameter. Heavy duty.
Drive	High torque motor, with relief valve protection, chain drive. Reversible.
Optional	Water sprinkler unit - 230 litre capacity.

Model	Mount	Sweeping Width	Width	Depth	Height
FTX-180	Front	1.73m	1.88m	1.27m	0.83m
FTX -210	Front	2.12m	2.27m	1.27m	0.83m
FTX -240	Front	2.43m	2.58m	1.27m	0.83m

