



- High torque direct drive motor.
- Relief valve motor protection.
- Reversible brush drive.
- Manual angling – left or right.
- Heavy duty steel construction.
- Single hydraulic service operation.
- Heavy duty castors.
- Rear '3 point linkage' mounting.
- Parking stand.
- Quick change brush.
- Choice of brush bristle.
- Choice of 2 sweeping widths.



Combining robust construction with sheer sweeping power, the RTX-HYD makes light work of any sweeping task. This versatile unit is tractor '3 point linkage' mounted, hydraulically driven and available in two sweeping widths to meet your exact requirements. The high torque hydraulic drive is reversible and fitted with a pressure relief valve to protect the motor seals. The unit has an integrated parking stand for storage and servicing when not in use.

Use	Heavy – Extra heavy duty sweeping
Mounting	Tractor rear '3 point linkage' CAT 2.
Power Source	Hydraulic: 40 - 70 litres/min flow rate @ min 140 BAR.
Brush adjustment	Heavy duty, height adjustable castor wheels.
Brush spec	560mm Diameter : Poly, or Poly/wire mix.
Angling	Manual. 20 degrees left or right.
Castors	203mm Diameter. Heavy duty.
Drive	High torque motor, with relief valve protection. Reversible direct drive.

Model	Mount	Sweeping Width	Width	Depth	Height
RTX-200 HYD	Rear	1.95m	2.23m	1.3m	1.08m
RTX-240 HYD	Rear	2.35m	2.63m	1.3m	1.08m

